

Technical Data Sheet

Capatue™ SCA-K02X

Abstract

SCA-K02X is a new type organo-functional silane which contains 2 silyl groups, this unique structure enable it to have a better adhesion to dry/wet surfaces, stronger and weather resistance bond.

Chemical Name

1,2-Bis(triethoxysilyl)ethane

CAS Registry Number

16068-37-4


EINECS

240-212-2

Molecular Formula

$C_{14}H_{34}O_6Si_2$

Molecular Structure



Molecular Weight

354.59

Equivalents

Product	Supplier
Silquest® Y-9805	Momentive (formerly OSi Specialties)

Typical Properties

Index	Value
Appearance:	Colorless to light yellow transparent

[Http://www.capatue.com](http://www.capatue.com) E-mail: info@capatue.com

Tel: +86-25-8637 1192, 8637 1193 Fax: +86-25-8637 1191 ext. 0

Add: Block E4, Zidong Industry Park, 2 Zidong Road, Maqun Town, Qixia Dist., Nanjing, Jiangsu, China, 210023

GC Purity	≥ 95
Specific Gravity	0.958
Boiling point, °C	119
Flash point, °C	113
Water solubility:	REACTS

Applications and Performance

1, 2-Bis(triethoxysilyl)ethane (CAS No. 16068-37-4), Silane coupling agent SCA-K02X, has some application as below:

1. RTV silicone sealants: To enhance the adhesion to the dry or wet surfaces and could form a stronger and weather resistance bond.

2. Metal surface treatment: The toxic properties of chromates have caused an environmental demand on replacement of the chromium (VI) compound coating processes (chromating). One of the suggested methods is a silane coating. SCA-K02X with bis-silyl functional has six hydrolyzable groups and are believed to be more crosslinked than triand tetra-functional analogs. The enhanced crosslinking leads to better barrier properties in anticorrosion applications.

Packing

The regular packing of this product is 25kg plastic pail, 200L steel drums and 1000L immediate bulk container.

Storage and Shelf Life

Should be stored in dry, cool, ventilated room; keep away from water, moisture, high temperature and fire. This product has a shelf life of at least 12 months if stored in tightly closed original container at room temperature.

If this product is kept beyond the shelf life recommend on the product label, it is not necessarily unusable, but a quality control should be performed on the properties relevant to the application.

Product Safety and Handling

When considering the use of any Capatue products in a particular application, you should read our latest Material Safety Data Sheets (MSDS) thoroughly for handling instructions, personal protective equipment if necessary, other safety issue and toxicological data as well as for information on proper transportation, storage and use to ensure that the use you intend can be accomplished safely. Our latest Material Safety Data Sheets (MSDS) and other product safety information are available at www.capatue.com or upon request, from our customer service department.

Use of other material in conjunction with Capatue products may require addition precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

This product is for industry use only; it is neither tested nor represented as suitable for food, medical or pharmaceutical uses.

Limited Warranty Information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Capatue's products are safe, effective, and fully satisfactory for the intended end use.

Suggestions of use shall not be taken as inducements to infringe any patent.

Capatue's sole warranty is that the product will meet the Capatue sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Capatue specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Capatue disclaims liability for any incidental or consequential damages.

Customer must do enough tests before their regular production to ensure that our product is suitable for their specific application.